Product parameters

Model	M300
Rated Power	300W
Capacity	266.4Wh (22.2V/12Ah or 3.7V/72000mAh)
Battery type	UL certified car gauge grade Li-ion battery
Power Indicate	LCD display
LCD Display	Battery remaining capacity, battery failure, total output power excessive temperature, input power
DC input	DC15V/4A(60W Max)
DC fully Charging Time	About 5～6H
Solar Controller Model	MPPT
Solar Charging Input	18-23V/3A(60W max)
Charging temperature range	32~104°F(0°C~40°C)
USB output	Type-C output:PD 60W(5V3A,9V3A,12V3A,15V3A,20V3A)*1 USB output:QC3.0(18W/5V3A,9V2A,12V1.5A)*3(total 54W)
Cigarette lighter output	12V/10A(120W)
DC output	12V/5A/DC5521*2(total 120W)
LED lights	5W*2(total 10W Max) SOS,flshlingt
Discharge temperature range	14~104°F(-10~40°C)
Product size weight	273*181*244mm/about 3.95kg

Packing list

18V-23V Mc4 connector cable



60W power supply adapter

12V-14V car charger cable



Instruction manual

MINKO (SZ) TECHNOLOGY CO., LIMITED

+8613539872669 yumiko@szminko.com evstationcharger.com

309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ